

**City of Negaunee
PO Box 70
319 W. Case Street
Negaunee, MI 49866
906 475-9991**

INVITATION FOR BIDS

Sealed bids will be received by the City of Negaunee located at 319 W. Case Street, Negaunee, Michigan, 49866 until 1:00PM, April 24, 2023, for **Level 2 Outdoor Vehicle Charing Stations** for the Negaunee Downtown Enhancement Project.

Bid shall be submitted and addressed to the Negaunee City Clerk, City of Negaunee, PO Box 70, 319 W. Case Street, Negaunee, MI 49866. Envelope shall be sealed and clearly marked "**Level 2 Outdoor Vehicle Charing Stations**"– Negaunee Downtown Enhancement Project." Bids must be received before or by the above date and time. No fax or email bids will be accepted.

Bids will be opened on April 24, 2023, at 1:00PM at **319 W. Case Street (City Hall), second floor conference room.**

The City reserves the right to accept any or all bids or accept any part of a bid. Each of the items may be purchased individually or as a lump sum bid.

BID FORM

Vendor: _____

Address: _____

City of Negaunee – Streetlight Vendor				
Item Description	Quantity	Unit	Unit Price	Total Price
Item 1	2	Each		
Item 2 (total shipping)		Each		

TOTAL BID

\$

Item 1: Outdoor Dual Vehicle Charging Station, ZEFNET Standard Series or Alternative approved by owner, (priced by unit)

Pricing must include 5-year product warranty, 5-year technical support, 5-year cellular service & 5-year software license

Product Specifications

Model No.:	2 x ZEFNET-100-C
Pedestal Model No.:	CS-PDL-DMKT
kW Rating:	38.4 kW
Circuit Breaker Rating:	2 x 100A
Max. Current per Circuit:	80A
Communication Type:	Cellular or WiFi
Dimensions:	4.5"d x 44"h x 21"w includes (2) connector holsters (only 10.2" w without)
Certifications:	ETL, cETL Listed
Service:	208V to 240V - 40A to 80A, single phase, 2 wire w/ground
Charge current output power:	208V to 240V-32A to 64A continuous (7.7kW to 15.4kW)
Service ground monitor:	Constantly checks for presence of proper safety ground
Automatic circuit reclosure:	After minor power faults
Charge circuit interruption device:	Ground fault protection with fully automated self-test, eliminates manual user testing
25-foot charging cable (both sides)	
Install hardwired or plug-in Indoor/outdoor rated fully sealed (NEMA 4) enclosure	
Operating temperatures: -22°F to 122°F (-30°C to 50°C)	
Unit Branding Capabilities	

Item 2: Shipping (priced by shipping source)

Shipping by source

Delivered to:600 Cherry Street, Negaunee, Michigan 49866